

BISAZZA

CEMENTILES

MAINTENANCE INSTRUCTIONS

First treatment

After removing the cotton cloth or wadding which protected the surface during the works, wax the clean and dry floor using a microfiber cloth with Fila Matt* thus diluted: 80% wax and 20% water.

Routine cleaning

Clean the floor on a regular basis using water and a low-residue neutral detergent (Fila Cleaner* or other specific cleaners for marble or stone), and then rinse thoroughly.

DO NOT use aggressive detergents, like ammonia, bleach, limescale removers, alcohol and products with PH higher than 8.0.

Special maintenance

Use a microfiber cloth to apply a coat of diluted (50%) finishing wax Fila Matt* on the dry and clean floor. The wax treatment frequency depends on the floor use: higher for commercial spaces and lower for residential rooms.

Whether it would be necessary to remove the protective wax because of some stains left from the use, we recommend to wash with pure Fila PS87*. Then, once the floor is dry, reapply a layer of pure Fila Matt* wax.

Warnings

DO NOT sand the Bisazza cement tile floor.

Clean any stains immediately with water or neutral cleansers (i.e. Fila Cleaner*).

The surface waxing process must be repeated to ease the product cleaning.

Original tile colours may fade with exposure to sunlight.

Areas of application

Internal floors and walls for residential use.

Internal floors and walls for commercial use with moderate traffic.

Not recommended for wet rooms (showers, steam rooms, etc.)

* Refer to the manufacturer's technical data sheets.